

aspero

TYPE II
WALLCOVERING

TYPE II High durability, CCC-W-408D and W-101

WEIGHT 21 oz/ly (651 g/lm)

WIDTH 54" (137 cm)

CONTENTS 100% vinyl

BACKING Osnaburg

PATTERN MATCH Reverse hang, random match

FIRE TEST ASTM E-84 Tunnel Test: Class A, flame spread 20, smoke developed 35 (test procedure is comparable to NFPA 255 and UL 723)

UL 723 Tunnel Test: flame spread 10, smoke developed 5

CAN/ULC S102 Tunnel Test: flame spread 10, smoke developed 5

NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

LOW VOC California Section 01350

Can contribute to LEED® EQ Credit 4.1 for low-emitting materials, adhesives and sealants, if used with low-VOC adhesives

CONSTRUCTION WASTE MANAGEMENT May be recyclable through reclamation

MICROVENTING AVAILABLE This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

ADDITIONAL PRODUCT ATTRIBUTES

Antimicrobial additives

Cadmium and mercury free

Contains no heavy metals

Free of PBDE's (Brominated Flame Retardants)

IMO (International Maritime Organization) Available

Manufacturing materials recovery and reuse program

Water-based inks

CUSTOM CAPABILITIES Custom colors and weights are available

WARRANTY Manufacturer warrants to the customer that the product will be free from defects in material and workmanship for a period of three years from the date of sale

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

