

exclusive

decora

TYPE II
WALLCOVERING

TYPE II High durability, CCC-W-408D and W-101

WEIGHT 20 oz/ly (620 g/lm)

WIDTH 54" (137 cm)

CONTENTS 100% vinyl

BACKING Osnaburg

PATTERN MATCH Non-reverse hang, random match

FIRE TEST ASTM E84 Tunnel Test: Class A, flame spread 15, smoke developed 120 (test procedure is comparable to ANSI 2.5, NFPA 255, UBC 42-1 and UL 723)

CAN/ULC S102 Tunnel Test: flame spread 0, smoke developed 30

NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

European Standard EN 13823 Fire Test: meets requirements

LOW VOC California Section 01350

CONSTRUCTION WASTE MANAGEMENT May be recyclable through reclamation

MICROVENTING AVAILABLE This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

ADDITIONAL PRODUCT ATTRIBUTES

Cadmium and mercury free
Contains no heavy metals
Does not contain DEHP plasticizers
Free of PBDE's (Brominated Flame Retardants)
Water-based inks

CUSTOM CAPABILITIES Custom colors and weights are available

WARRANTY Manufacturer warrants that for a period of five years from the sale of its wallcovering products that the products shall be free of manufacturing defects, and that products shall not separate from their backings, and/or exhibit stains caused by bleeding of impurities

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

