

TOWER



54" / Type II / 20 oz. low voc T2-FT-08 Quill

Flutter

Physical Properties

WEIGHT: 20.0 oz. PLY/620 G/PLM 13.3 oz. PSY/451 G/PSM

WIDTH: 54"/137 cm MATCH: Reverse, random

BACKING: Osnaburg

Custom colors, weights, and micro venting available
Meets or exceeds Federal Specification CCC-W-408D

Fire Safety

- Class "A" Fire rated-Tested in accordance with ASTM E-84 Tunnel Test
- Passes Class "A" NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test
- Tested in accordance with CAN/ULC S102.2

Environment & Health

- 10% recycled content (varied blend of pre-consumer and remanufactured material)
- Certified to NSF/ANSI 342 Sustainability Assessment: ask distributor for details
- Meets California Section 01350 IAQ test requirements for wall covering
- Complies with USGBC LEED v4 Criteria, under Indoor Environmental Quality (CDPH/EHLB/Standard Method Version 1.1, 2010)

Warranty

5 year warranty against manufacturing defects.
Additional information is available www.towerwallcovering.com

D.L.Couch

800 433 0790

Eykon

800 222 7866

tri|kes

800 200 8120

© J • JOSEPHSON