

# gilded

RECYCLED TYPE II  
WALLCOVERING

**TYPE II** High durability, CCC-W-408D and W-101

**WEIGHT** 20 oz/ly (620 g/lm)

**WIDTH** 52" (132 cm)

**CONTENTS** 100% vinyl

**RECYCLED CONTENT** 10% pre-consumer recycled content by weight

**BACKING** Osnaburg

**PATTERN MATCH** Reverse hang, 52" (132 cm) horizontal repeat, 18" (45.5 cm) vertical repeat, straight across match (look for the arrows in the selvage for alignment)

**FIRE TEST** ASTM E84 Tunnel Test: Class A, flame spread 20, smoke developed 45 (test procedure is comparable to NFPA 255 and UL 723)

CAN/ULC S102 Tunnel Test: flame spread 0, smoke developed 45

NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

**LOW VOC** California Section 01350

**CONSTRUCTION WASTE MANAGEMENT** May be recyclable through reclamation

**MICROVENTING AVAILABLE** This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

#### ADDITIONAL PRODUCT ATTRIBUTES

Antimicrobial additives  
Cadmium and mercury free  
Contains no heavy metals  
Does not contain DEHP plasticizers  
Free of PBDE's (Brominated Flame Retardants)  
Solvent-based inks

**CUSTOM CAPABILITIES** Custom colors and weights are available

**WARRANTY** Five-year warranty against manufacturing defects

**PRODUCT USE ADVISORY** This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

**SPECIAL INSTALLATION INSTRUCTION** For best results, the drywall surface should be finished to a level 4 prior to installation

