TOWER



54"/ Type II / 20 oz. low voc T2-LT-40 Emerald

Lorelei Texture

Physical Properties

WEIGHT: 20.0 oz. PLY/620 G/PLM 13.3 oz. PSY/451 G/PSM MATCH: Reverse, random WIDTH: 54"/137 cm BACKING: Osnaburg

Custom colors, weights, and micro venting available Meets or exceeds Federal Specification CCC-W-408D

Fire Safety

- Class "A" Fire rated-Tested in accordance with ASTM E-84 Tunnel Test •
- Passes Class "A" NFPA 101 Life Safety Code •
- Passes NFPA 286 Corner Burn Test
- Tested in accordance with CAN/ULC S102.2 •

See website or contact us for additional results


Environment & Health

- 10% recycled content (varied blend of pre-consumer and remanufactured material)
- Certified to NSF/ANSI 342 Sustainability Assessment: ask distributor for details
- Meets California Section 01350 IAQ test requirements for . wall covering
- Complies with USGBC LEED v4 Criteria, under Indoor Environmental Quality (CDPH/EHLB/Standard Method Version 1.1, 2010)

Warranty

5 year warranty against manufacturing defects. Additional information is available www.towerwallcovering.com

D.L.Couch Eykon 800 433 0790



800 200 8120

©J•JOSEPHSON