

# luca

TYPE II  
WALLCOVERING

**TYPE II** High durability, CCC-W-408D and W-101

**WEIGHT** 20 oz/ly (620 g/lm)

**WIDTH** 54" (137 cm)

**CONTENTS** 100% vinyl

**RECYCLED CONTENT** 7% post-consumer recycled content by weight (non-woven backing)

**BACKING** Non-woven

**PATTERN MATCH** Non-reverse hang, 25 1/4" (64 cm) vertical repeat, straight across match

**FIRE TEST** ASTM E84 Tunnel Test: Class A, flame spread 25, smoke developed 45 (test procedure is comparable to UL 723)

CAN/ULC S102 Tunnel Test: flame spread 10, smoke developed 5

**LOW VOC** California Section 01350

**CONSTRUCTION WASTE MANAGEMENT** May be recyclable through reclamation

**MICROVENTING AVAILABLE** This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

**ADDITIONAL PRODUCT ATTRIBUTES**

Cadmium and mercury free  
Contains no heavy metals  
Water-based inks

**CUSTOM CAPABILITIES** Custom colors are available

**WARRANTY** Manufacturer warrants that for a period of five years from the shipment of its commercial wallcovering products, products shall not exhibit color fading, delamination of backing, or mildew migration stains when products are installed following manufacturer's instructions on a structurally stable, properly prepared wall maintained at normal room temperatures (60 to 80 degrees F).

**PRODUCT USE ADVISORY** This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

