

# mercER

TYPE II  
WALLCOVERING

**TYPE II** High durability, CCC-W-408A and W-101

**WEIGHT** 20 oz/ly (620 g/lm) equivalent to 54" (137 cm) material

**WIDTH** 41 3/4" (106 cm)

**CONTENTS** 100% vinyl

**BACKING** Non-woven

**PATTERN MATCH** Non-reverse hang, random match

**FIRE TEST** ASTM E84 Tunnel Test: Class A, flame spread 25, smoke developed 35 (test procedure is comparable to UL 723)

European Standard EN 13501 Fire Test: meets requirements

**ADDITIONAL TESTS** European Community Certificate of Conformity IMO/MED 1121

**CONSTRUCTION WASTE MANAGEMENT** May be recyclable through reclamation

**MICROVENTING AVAILABLE** This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

**SPECIAL NOTE** Please note that this material is not returnable

#### ADDITIONAL PRODUCT ATTRIBUTES

Bio-Pruf™ antimicrobial additives  
Cadmium and mercury free  
Contains no heavy metals  
Does not contain DEHP plasticizers  
Free of PBDE's (Brominated Flame Retardants)  
Water-based inks

#### MANUFACTURING

ISO 14001  
IGI Quality Mark  
International Pollution Prevention and Control (IPPC)

**WARRANTY** Manufacturer warrants that for a period of 3 years wallcovering is guaranteed to be first quality and free of manufacturing defects. This warranty applies only on professionally installed wallcoverings as advised in hanging instructions.

**PRODUCT USE ADVISORY** This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

