



## MERINO SILK

---

## PATTERN PROFILE

**TYPE II** High Durability, CCC-W-408D and W-101

**WEIGHT** 25 oz/ly (775 g/lm)

**WIDTH** 52-54" (132-137 cm)

**CONTENTS** 100% Vinyl

**BACKING** Cotton Scrim

**PATTERN MATCH** Reverse hang, random match

**FIRE TEST** ASTM E-84 Tunnel Test: Class A, flame spread 5, smoke developed 40, NFPA 286 Corner Burn, NFPA 101 Life Cycle Safety Code

**MICROVENTING AVAILABLE** This product can be microvented for breathability. Contact distributor for minimums.

**CUSTOM CAPABILITIES** Custom colors are available

### ADDITIONAL PRODUCT ATTRIBUTES

Low VOC, Meets California Section 01350  
Indoor Air Quality Standard

Can contribute to LEED® EQ 4.1 point for low-emitting materials, adhesives, and sealants if used with low VOC adhesives

Can contribute to LEED® MR 5.1 point for regional materials.

Made with highly cleanable water-based inks.

Contains no cadmium or mercury-based pigments.

Pigments are fade and alkali-resistant. Made in the USA

Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM-G21.

These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.

**PRODUCT USE ADVISORY** This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within the walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.