

# mirth

TYPE II  
WALLCOVERING

**TYPE II** High durability, CCC-W-408D and W-101

**WEIGHT** 20 oz/ly (620 g/lm)

**WIDTH** 54" (137 cm)

**CONTENTS** Vinyl, polyester/metal

**BACKING** Non-woven

**PATTERN MATCH** Reverse hang, random match

**FIRE TEST** ASTM E-84 Tunnel Test: Class A, flame spread 15, smoke developed 135 (test procedure is comparable to ANSI 2.5, NFPA 255, UBC 42-1 and UL 723)



NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

European Standard EN 13501 Fire Test: meets requirements

**LOW VOC** California Section 01350

**MICROVENTING AVAILABLE** This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

**SPECIAL NOTE** Please be aware that this wallcovering may interfere with broadcast signals, such as Wi-Fi and radio reception. While interference is possible because of the polyester/metal layer in this specific construction, tests have shown a 5% or less impact on signals when the receptor is totally encased in wallcovering.

#### ADDITIONAL PRODUCT ATTRIBUTES

Cadmium and mercury free  
Contains no heavy metals  
Does not contain DEHP plasticizers  
Free of PBDE's (Brominated Flame Retardants)  
Water-based inks

**CUSTOM CAPABILITIES** Custom colors and weights are available

**WARRANTY** Manufacturer warrants that for a period of five years from the sale of its wallcovering products that the products shall be free of manufacturing defects, and that products shall not separate from their backings, and/or exhibit stains caused by bleeding of impurities

**PRODUCT USE ADVISORY** This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

**SPECIAL INSTALLATION INSTRUCTION** This wallcovering contains metallic particles and will conduct electricity. To avoid possible fire hazards or electric shock, wallcovering should not come in contact with or extend into electrical-outlet boxes or light-switch boxes. Turn off all electricity to the room prior to starting installation. For best results, the drywall surface should be finished to a level 4 prior to installation and the material should be hung using clay-based adhesive for maximum tack.