

exclusive

muir

TYPE II
WALLCOVERING

TYPE II High durability, CCC-W-408D and W-101

WEIGHT 20 oz/ly (620 g/lm)

WIDTH 54" (137 cm)

CONTENTS 100% vinyl

RECYCLED CONTENT 11% post-consumer recycled content by weight (non-woven backing)

BACKING Non-woven

PATTERN MATCH Reverse hang, random match

FIRE TEST ASTM E84 Tunnel Test: Class A, flame spread 10, smoke developed 25 (test procedure is comparable to NFPA 255, UBC 8-1 and UL 723)

CAN/ULC S102 Tunnel Test: flame spread 0, smoke developed 31

NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

European Standard EN 13501 Fire Test: meets requirements

LOW VOC California Section 01350

CONSTRUCTION WASTE MANAGEMENT May be recyclable through reclamation

MICROVENTING AVAILABLE This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

ADDITIONAL PRODUCT ATTRIBUTES

Cadmium and mercury free
Contains no heavy metals
Does not contain DEHP plasticizers
Free of PBDE's (Brominated Flame Retardants)
Water-based inks

CUSTOM CAPABILITIES Custom colors and weights are available

WARRANTY Manufacturer warrants that for a period of five years from the sale of its wallcovering products that the products shall be free of manufacturing defects, and that products shall not separate from their backings, and/or exhibit stains caused by bleeding of impurities

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.



D.L.Couch
800 433 0790

Eykon
800 222 7866

trikes
800 200 8120