

PATTERN INFORMATION

Type:	Type II
Width:	52/54" (132/137 cm)
Weight:	20 oz per lineal yard
Backing:	Osnaburg
Installation:	Reversible pattern with a random match
Vertical Repeat:	Not applicable
Horizontal Repeat:	Not applicable
Custom Colors/Weights Available*:	Type I or Type II: 1,000 yard min.
Minimum Custom Weight/Backing*:	Type I: 15oz scrim (Not Second Look construction) Type II: 20oz osnaburg (Second Look construction)
Custom Microventing (Perforation) available*:	Contact distributor for minimums

*Subject to Custom Production Coverage %

PATTERN SPECIFICATIONS

	U.S.	Metric
Finished Total Weight:		
*19.5 oz per lineal yard	20 oz/ly	620 g/lm
*13.0 oz per square yard	13.3 oz/sq yd	452 g/sq m
Vinyl Weight:		
*7.0 oz per square yard	10.3 oz/sq yd	349 g/sq m
Backing Fabric Weight:	1.8 oz/sq yd	61 g/sq m
Average Total Thickness:	.018"	.457 mm
Tensile Breaking Strength:	Exceeds min. Type II specification	
*50 x 55 lbs - 222 x 245 N		
Tear Strength:	Exceeds min. Type II specification	
*25 x 25 Scale Reading		
Average Adhesion Vinyl to Fabric:	Exceeds min. Type II specification	
*3lb/in - 13.4 N/25mm		

*Minimum specification requirement

FIRE CLASSIFICATION: CLASS A - ASTM E-84

Flame	15
Smoke	20
Passes NFPA 286 Corner Burn	
NFPA 101 Life Safety Code	
CAN/ULC S102-07	
EU Certificate of Conformity, CE Declaration of Conformity or Eurofire Certificate	Must be specified upon order

ENVIRONMENTAL

Manufactured using Second-Look® Recycled Wallcovering*:

- 20% recycled content by weight
- Aggressive manufacturing materials recovery and reuse program
- Recyclable through Second-Look Program



Visit LANARK.com for additional Second-Look and recycling program information

- Meets California Section 01350 Indoor Air Quality Standard
- Meets State of Washington Building Specification for Indoor Air Quality
- Printed with highly cleanable water-based inks
- Contains no cadmium or mercury-based pigments

USGBC LEED Support:

- MR - Materials and Resources - Recycled Content
- MR - Materials and Resources - Construction waste management
- EQ - Indoor Environmental Quality - Low emitting materials

*Second-Look® is a registered trademark of LSI Wallcovering

OTHER FEATURES

- Made in the USA
- High durability
- Fade resistant pigments, alkali resistant
- Vinyl wallcovering, by nature, is impermeable. Perforation available.



PRODUCT USE ADVISORY

This product is intended for use in buildings designed and maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it very low in permeability.

Vinyl wallcovering products should not be installed on walls that contain excessive moisture or are subject to moisture infiltration. If mold or mildew is present, or if walls show moisture damage or have excess moisture content, do not proceed with installation. Moisture infiltration and water vapor in and behind the wall must be eliminated for proper performance.

Processes that increase permeability, including microventing, should be considered for use under certain conditions in addition, the use of a mildew inhibitor in the primer and adhesive is highly recommended. Primers and adhesives with the highest possible permeability rating are also highly recommended.

After installation, the walls and wallcovering should be monitored for potential moisture or water vapor infiltration and accumulation. Any such infiltration or accumulation after installation must be promptly eliminated.



LANARK.COM

D.L.Couch

800 433 0790

Eykon

800 222 7866

tri|kes

800 200 8120