

preston

TYPE II
WALLCOVERING

TYPE II High durability, Fed. Spec. CCC-W-408D

WEIGHT 20 oz/ly (620 g/lm)

WIDTH 50" (127 cm)

CONTENTS 100% vinyl

BACKING Osnaburg

PATTERN MATCH Non-reverse hang, 50" (127 cm) horizontal repeat, 36" (91.5 cm) vertical repeat, straight across match

FIRE TEST ASTM E-84 Tunnel Test: Class A, flame spread 15, smoke developed 20 (test procedure is comparable to ANSI/UL 723, NFPA 255 and UBC 8-1)

CAN/ULC S102 Tunnel Test: flame spread 25, smoke developed 25

NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

CONSTRUCTION WASTE MANAGEMENT Recyclable through reclamation

MICROVENTING AVAILABLE This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

ADDITIONAL PRODUCT ATTRIBUTES

- Antimicrobial additives
- Cadmium and mercury free
- Contains no heavy metals
- Does not contain DEHP plasticizers
- Free of PBDE's (Brominated Flame Retardants)
- Manufacturing materials recovery and reuse program
- Solvent-based inks

SPECIAL NOTE Additional coordinating background textures available in Versa's Bristol pattern

CUSTOM COLORS AVAILABLE 60 linear yard (55 meter) minimum

WARRANTY Product is guaranteed to be free of defects in workmanship and material for five years

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

