

reese

RECYCLED TYPE II
WALLCOVERING

TYPE II High durability, CCC-W-408D and W-101

WEIGHT 20 oz/ly (620 g/lm)

WIDTH 54" (137 cm)

CONTENTS 100% vinyl

RECYCLED CONTENT 10% pre-consumer recycled content by weight

BACKING Osnaburg

PATTERN MATCH Reverse hang, random match



FIRE TEST ASTM E84 Tunnel Test: Class A, flame spread 20, smoke developed 45 (test procedure is comparable to NFPA 255 and UL 723)

CAN/ULC S102 Tunnel Test: flame spread 0, smoke developed 45

NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

LOW VOC California Section 01350

CONSTRUCTION WASTE MANAGEMENT May be recyclable through reclamation

MICROVENTING AVAILABLE This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

ADDITIONAL PRODUCT ATTRIBUTES

- Antimicrobial additives
- Cadmium and mercury free
- Contains no heavy metals
- Does not contain DEHP plasticizers
- Free of PBDE's (Brominated Flame Retardants)
- Solvent-based inks

CUSTOM CAPABILITIES Custom colors and weights are available

WARRANTY Five-year warranty against manufacturing defects

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.