

Specifications

VERSA™ Sakai pattern meets or exceeds all Type II requirements of CCC-W-408A/D and Industry Voluntary Standard CFFA-W-101A/D.

Specifications:	Performance:
Weight (Avg):	20 oz/ly (452 gr/M ²)
Width:	52/54" (132/137 cm)
Backing:	Osnaburg
Installation:	Reverse hang / Random match

Custom colors, weights, widths and microventing are available.

Fire Safety:

- Class A (ASTM E-84)
- Passes NFPA 286 Corner Burn
- NFPA 101 Life Safety Code

Environmental and Health:

- Recyclable through Versa's Second-Look™ Program
- Aggressive manufacturing materials recovery and reuse program
 - Highly cleanable water-based inks
- PFOA free – does not contain Perfluorooctanoic Acid
 - Cadmium and mercury free
- Free of PBDE's (Brominated Flame Retardants)
 - Does not contain DEHP Plasticizers
 - Antimicrobial additives

Moisture, Mold and Mildew:

Vinyl wallcovering functions as a vapor barrier. If water or moisture becomes trapped between the wallcovering and wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use of vinyl wallcovering.

A mildew inhibiting additive has been added to help protect against fungal and other microbiological growth. No additives however, will prevent mold growth if moisture is allowed to accumulate and its sources are not eliminated.

Further protection against mold growth may be achieved with Versa PermaVent™, a unique microventing technology that literally "breathes," helping manage the mobile moisture in walls.

Warranty:

VERSA™ is guaranteed to be free of defects in workmanship and material for five years.

For additional details on Second-Look, moisture management, PermaVent, warranty and other Versa innovations, visit our website at versawallcovering.com.

D.L.Couch

800 433 0790

Eykon

800 222 7866

trikes

800 200 8120



Versa wallcovering is recyclable when reclaimed through the Versa Second-Look recycling program.

All VERSA™ designs are copyrighted ©LSI Wallcovering versawallcovering.com

LSI
WALLCOVERING