

exclusive

# sequins

TYPE II  
WALLCOVERING

**TYPE II** High durability, Fed. Spec. CCC-W-408A

**WEIGHT** 20 oz/ly (620 g/lm)

**WIDTH** 54" (137 cm)

**BACKING** Osnaburg

**PATTERN MATCH** Reverse hang, random match

**FIRE TEST** ASTM E-84 Tunnel Test: Class A, flame spread 5, smoke developed 35 (test procedure is comparable to ANSI/UL 723, NFPA 255 and UBC 8-1)

CAN/ULC S102 Tunnel Test: flame spread 5, smoke developed 20

NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

**LOW VOC** California Section 01350, State of Washington  
Can contribute to LEED® EQ Credit 4.1 for low-emitting materials, adhesives and sealants, if used with low-VOC adhesives

**CONSTRUCTION WASTE MANAGEMENT** Recyclable through reclamation

**MICROVENTING AVAILABLE** This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

#### ADDITIONAL PRODUCT ATTRIBUTES

- Antimicrobial additives
- Cadmium and mercury free
- Contains no heavy metals
- Does not contain DEHP plasticizers
- Free of PBDE's (Brominated Flame Retardants)
- IMO (International Maritime Organization) Available
- Manufacturing materials recovery and reuse program
- Water-based inks

**CUSTOM CAPABILITIES** Custom colors, weights and widths are available

**WARRANTY** Product is guaranteed to be free of defects in workmanship and material for five years

**PRODUCT USE ADVISORY** This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

