

exclusive

stitched leather

TYPE II
WALLCOVERING

TYPE II High durability, Fed. Spec. CCC-W-408A

WEIGHT 20 oz/ly (620 g/lm)

WIDTH 54" (137 cm)

BACKING Osnaburg

PATTERN MATCH Reverse hang, 7.283" (18.5 cm) vertical repeat, drop match

FIRE TEST ASTM E-84 Tunnel Test: Class A, flame spread 5, smoke developed 35 (test procedure is comparable to ANSI/UL 723, NFPA 255 and UBC 8-1)



CAN/ULC S102 Tunnel Test: flame spread 5, smoke developed 20

NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

LOW VOC California Section 01350, State of Washington

Can contribute to LEED® EQ Credit 4.1 for low-emitting materials, adhesives and sealants, if used with low-VOC adhesives

CONSTRUCTION WASTE MANAGEMENT Recyclable through reclamation

MICROVENTING AVAILABLE This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

ADDITIONAL PRODUCT ATTRIBUTES

- Antimicrobial additives
- Cadmium and mercury free
- Contains no heavy metals
- Does not contain DEHP plasticizers
- Free of PBDE's (Brominated Flame Retardants)
- Manufacturing materials recovery and reuse program
- Water-based inks

CUSTOM CAPABILITIES Custom colors, weights and widths are available

WARRANTY Product is guaranteed to be free of defects in workmanship and material for five years

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.