

exclusive

valencia

TYPE II
WALLCOVERING

TYPE II High durability, CCC-W-408A and W-101

WEIGHT 20 oz/ly (620 g/lm)

WIDTH 54" (137 cm)

CONTENTS 100% vinyl

RECYCLED CONTENT 7% post-consumer recycled content by weight (non-woven backing)

BACKING Non-woven

PATTERN MATCH Reverse hang, random match

FIRE TEST ASTM E84 Tunnel Test: Class A, flame spread 10, smoke developed 10 (test procedure is comparable to UL 723)

CAN/ULC S102 Tunnel Test: flame spread 25, smoke developed 65

NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

ENVIRONMENTAL STANDARDS
Environmental Product Declaration (EPD)

HEALTH STANDARDS
California Section 01350
CHPS
SCS Indoor Advantage™ Gold
Health Product Declaration (HPD)

CONSTRUCTION WASTE MANAGEMENT May be recyclable through reclamation

MICROVENTING AVAILABLE This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

ADDITIONAL PRODUCT ATTRIBUTES Antimicrobial additives, Cadmium and mercury free, Contains no heavy metals, Does not contain DEHP plasticizers, Free of PBDE's (Brominated Flame Retardants), Phthalate free, Manufacturing materials recovery and reuse program, Water-based inks

CUSTOM CAPABILITIES Custom colors, weights and widths are available

WARRANTY Manufacturer warrants that for a period of five years from the installation of its commercial wallcovering there shall not be separation from their backings, exhibit stains caused by bleeding of impurities or support the growth of mildew when wallcoverings are installed properly on a sound wall, adequately maintained and used under normal conditions

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

SPECIAL INSTALLATION INSTRUCTION For best results, the drywall surface should be finished to a level 5 prior to installation

