



WIDTH 54" (137 cm) plus selvage

CONTENTS 57% olefin, 40% polyester, 3% nylon

BACKING Acrylic

FINISH Crypton® INCASE™

PATTERN MATCH Non-reverse hang, random match

FIRE TEST ASTM E-84 Tunnel Test: Class A, flame spread 15, smoke developed 10 (test procedure is comparable to UL 723)

COLORFASTNESS

AATCC-16 Colorfastness to Light: Class 4.5, 40 hours

AATCC-8 Colorfastness to Wet & Dry Crocking: meets requirements

TENSILE STRENGTH ASTM D5034: meets requirements

CUSTOM CAPABILITIES Custom backing is available

WARRANTY In no case shall we be liable for loss or damage resulting from normal wear and tear or incorrect handling or use. This also applies to use of the goods for purposes other than those for which they were developed or sold. In the event of seller's liability, buyer's sole and exclusive remedy will be limited to replacement by seller of any defective or non-conforming goods. Seller expressly disclaims any liability to buyer, its customers or to end users of its products for special, incidental, punitive or consequential damages to or loss of other property or equipment, personal injury, loss of profits, business or revenues, or cost or other damage, loss or expense from any cause whatsoever, arising out of or in any way connected with the sale or use of its products. The maximum liability, if any, of seller for all damages hereunder is limited to the purchase price of defective or non-conforming products. Any action arising hereunder must be brought within one year from the date of sale.

