

stylized weave

TEXTILE
WALLCOVERING

WIDTH 54" (137 cm)

CONTENTS 55% cotton, 45% viscose

RECYCLED CONTENT 7% post-consumer recycled content by weight (polyester backing)

CERTIFIED WOOD FSC certified (wood pulp backing)

RAPIDLY RENEWABLE MATERIALS Cotton and viscose (cellulose based)

BACKING Paper (70% wood pulp, 30% polyester)

FINISH Stain repellent

PATTERN MATCH Non-reverse hang unless otherwise noted on the roll, random match

FIRE TEST ASTM E84 Tunnel Test: Class A, flame spread 20, smoke developed 55 (test procedure is comparable to NFPA 255 and UL 723)

European Standard EN 13501 Fire Test: meets requirements

LIGHTFASTNESS ISO 105-B, method 1, Heraeus original Hanau Xenotest 150S, minimum 7 on the standard blue scale

PERMEABILITY ASTM E96 Water Vapor Transmission Rate: meets requirements

LOW VOC ASTM D5116/D5197/D6196: meets requirements

SPECIAL NOTE These fabrics have been manufactured using mainly natural fibers. Any slubs, impurities and irregularities in texture and color are characteristic of these natural yarns and enhance the nature of the fabric and cannot be considered a fault. There can be a variation between the sample material and the delivered product.

Please note that this material is not returnable.

ADDITIONAL PRODUCT ATTRIBUTES All dyeing, printing, laminating, finishing, etc., is totally water based

WARRANTY Manufacturer warrants that for a period of five years from the delivery of its wallcovering, products shall not separate from their backings when properly installed on a sound interior wall, adequately maintained and used under normal conditions

