

# tessellation suede

TEXTILE  
WALLCOVERING

**WIDTH** 54" (137 cm)

**CONTENTS** 100% polyester

**RECYCLED CONTENT** 7.3% post-consumer recycled content by weight (polyester backing)

**CERTIFIED WOOD** FSC certified (wood pulp backing)

**BACKING** Paper (70% wood pulp, 30% polyester)

**FINISH** Stain repellent

**PATTERN MATCH** Non-reverse hang unless otherwise noted on the roll, 2 1/2" (6 cm) horizontal repeat, 2 1/2" (6 cm) vertical repeat, straight across match

**FIRE TEST** ASTM E84 Tunnel Test: Class A, flame spread 20, smoke developed 50 (test procedure is comparable to NFPA 255 and UL 723)

European Standard EN 13501 Fire Test: meets requirements

**LIGHTFASTNESS** ISO 105-B, method 1, Heraeus original Hanau Xenotest 150S, minimum 5 on the standard blue scale

**PERMEABILITY** ASTM E96 Water Vapor Transmission Rate: meets requirements

**LOW VOC** ASTM D5116/D5197/D6196: meets requirements

**SPECIAL NOTE** As with real suede, this quality has a nap which can occasionally produce a slight paneling effect. Handling or touching changes the direction of the nap, but this can be eliminated by brushing the nap in the same direction with a soft clothes brush. There can be a variation between the sample material and the delivered product.

Please note that this material is not returnable.

**ADDITIONAL PRODUCT ATTRIBUTES** All dyeing, printing, laminating, finishing, etc., is totally water based

**WARRANTY** Manufacturer warrants that for a period of five years from the delivery of its wallcovering, products shall not separate from their backings when properly installed on a sound interior wall, adequately maintained and used under normal conditions

