

WIDTH 54" (137 cm) plus selvage

CONTENTS 100% polyester yarns

RECYCLED CONTENT 30% post-consumer,

55% pre-consumer

BACKING Acrylic/latex

FINISH Crypton® Green

ABRASION RESISTANCE ASTM D4157: 100,000 double rubs

FIRE TEST ASTM E-84 Tunnel Test: Class A, flame spread 25, smoke developed 25 (test procedure is comparable to ANSI/UL 723, NFPA 255 and UBC 8-1)



UBC 42-2 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

COLORFASTNESS

AATCC-16 Colorfastness to Light: Class 5, 40 hours

AATCC-8 Colorfastness to Wet & Dry Crocking: meets requirements Colorfastness to Water & Solvents: meets requirements

PERMEABILITY ASTM E96 Water Vapor Transmission Rate: meets requirements

TEAR STRENGTH ASTM D2261: meets requirements

TENSILE STRENGTH ASTM D5034: meets requirements

SOUND ABSORPTION ASTM C423 Reverberation Room Method: noise reduction coefficient (NRC) 1.05, sound absorption average (SAA) 1.07

ADDITIONAL TESTS ASTM D434 Seam Slippage: meets requirements

LOW VOC GREENGUARD Certified, GREENGUARD Gold

Can contribute to LEED® EQ Credit 4.1 for low-emitting materials, adhesives and sealants, if used with low-VOC adhesives

CONSTRUCTION WASTE MANAGEMENT Recyclable through reclamation

ADDITIONAL PRODUCT ATTRIBUTES Manufacturing materials recovery and reuse program

CUSTOM CAPABILITIES Custom backing is available

WARRANTY Product is certified to be free of manufacturing defects for a period of two years from date of purchase when installed according to manufacturer's installation instructions



