

clothier

TYPE II
WALLCOVERING

TYPE II High durability, CCC-W-408A and W-101

WEIGHT 20 oz/ly (620 g/lm) equivalent to 54" (137 cm) material

WIDTH 51 1/8" (130 cm)

CONTENTS 100% vinyl

BACKING Textile fabric weave (cotton)

PATTERN MATCH Non-reverse hang, random match

FIRE TEST ASTM E84 Tunnel Test: Class A, flame spread 25, smoke developed 60 (test procedure is comparable to UL 723)

European Standard EN 13501 Fire Test: meets requirements

ADDITIONAL TESTS European Community Certificate of Conformity IMO/MED 1121

CONSTRUCTION WASTE MANAGEMENT May be recyclable through reclamation

MICROVENTING AVAILABLE This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

SPECIAL NOTE Please note that this material is not returnable

ADDITIONAL PRODUCT ATTRIBUTES

Bio-Pruf™ antimicrobial additives
Cadmium and mercury free
Contains no heavy metals
Does not contain DEHP plasticizers
Free of PBDE's (Brominated Flame Retardants)
Water-based inks

MANUFACTURING

ISO 14001
IGI Quality Mark
International Pollution Prevention and Control (IPPC)

WARRANTY Manufacturer warrants that for a period of 3 years wallcovering is guaranteed to be first quality and free of manufacturing defects. This warranty applies only on professionally installed wallcoverings as advised in hanging instructions.

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

