

# concord

CRYPTON®  
RECYCLED  
WALLCOVERING

**WIDTH** 54" (137 cm) plus selvage

**CONTENTS** 100% recycled polyester yarns

**RECYCLED CONTENT** 44% post-consumer,  
56% pre-consumer

**BACKING** Acrylic/latex

**FINISH** Crypton® Green

**ABRASION RESISTANCE** ASTM D4157: 100,000 double rubs

**FIRE TEST** ASTM E-84 Tunnel Test: Class A, flame spread 25, smoke developed 25 (test procedure is comparable to ANSI/UL 723, NFPA 255 and UBC 8-1)

UBC 42-2 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

**COLORFASTNESS**

AATCC-16 Colorfastness to Light: Class 5, 40 hours

AATCC-8 Colorfastness to Wet & Dry Crocking: meets requirements  
Colorfastness to Water & Solvents: meets requirements

**PERMEABILITY** ASTM E96 Water Vapor Transmission Rate: meets requirements

**TEAR STRENGTH** ASTM D2261: meets requirements

**TENSILE STRENGTH** ASTM D5034: meets requirements

**SOUND ABSORPTION** ASTM C423 Reverberation Room Method: noise reduction coefficient (NRC) 1.05, sound absorption average (SAA) 1.07

**ADDITIONAL TESTS** ASTM D434 Seam Slippage: meets requirements

**LOW VOC** GREENGUARD Certified, GREENGUARD Gold

Can contribute to LEED® EQ Credit 4.1 for low-emitting materials, adhesives and sealants, if used with low-VOC adhesives

**CONSTRUCTION WASTE MANAGEMENT** Recyclable through reclamation

**ADDITIONAL PRODUCT ATTRIBUTES** Manufacturing materials recovery and reuse program

**CUSTOM CAPABILITIES** Custom backing is available

**WARRANTY** Product is certified to be free of manufacturing defects for a period of two years from date of purchase when installed according to manufacturer's installation instructions

