

coupe



HIGH DURABILITY Scrubbability, washability, tear and tensile strength meets or exceeds W-101 Type II

WIDTH 38 5/8" (98 cm)

ROLL LENGTH 11 linear yards (10 meters) sold in full rolls only

CONTENTS 100% coated glass fiber

PATTERN MATCH Reverse hang, random match

FIRE TEST ASTM E84 Tunnel Test: Class A, flame spread 20, smoke developed 5 (test procedure is comparable to UL 723)

CAN/ULC S102 Tunnel Test: flame spread 10, smoke developed 15

European Standard EN 13501 Fire Test: meets requirements

IMO Meets IMO (International Maritime Organization) requirements

PERMEABILITY ASTM E96 Water Vapor Transmission

SUSTAINABILITY OEKO-TEX® Standard 100, Novelio® CleanAir

LOW VOC California Section 01350, French VOC Regulation: meets requirements A+

MANUFACTURING ISO 9001, ISO 14001


WARRANTY Product is guaranteed to be free of defects in workmanship and material for five years



CleanAir technology removes formaldehyde from the air

How does it work?

1. FORMALDEHYDE ABSORPTION
2. PERMANENTLY CAPTURED
3. NEVER RELEASED



Low VOC

Breathable without perforation

- Woven glass fiber with natural breathability

Natural durability of decorated glass fiber

- Made with non-toxic chemicals certified by OEKO-TEX® Standard 100
- Lightweight for lower transport costs but as strong as a Type III vinyl wallcovering
- Perfectly colorfast
- Scrubbable and does not absorb water
- Impact resistant