

# leiden CRYPTON® | wall

**WIDTH** 54" (137 cm) plus selvage

**CONTENTS** 100% polyester

**RECYCLED CONTENT** 16% post-consumer recycled content by weight, 30% pre-consumer recycled content by weight

**BACKING** Acrylic/latex

**FINISH** Crypton® Wall

**PATTERN MATCH** Non-reverse hang, random match

**FIRE TEST** ASTM E84 Tunnel Test: Class A, flame spread 25, smoke developed 25 (test procedure is comparable to ANSI/UL 723, NFPA 255 and UBC 8-1)

CAN/ULC S102 Tunnel Test: flame spread 5, smoke developed 20

UBC 42-2 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

**COLORFASTNESS**

AATCC-16 Colorfastness to Light: Class 4.5, 40 hours

AATCC-8 Colorfastness to Wet & Dry Crocking: meets requirements

**PERMEABILITY** ASTM E96 Water Vapor Transmission Rate: meets requirements

**TEAR STRENGTH** ASTM D2261: meets requirements

**TENSILE STRENGTH** ASTM D5034: meets requirements

**ADDITIONAL TESTS**

ASTM D3511 Pilling: meets requirements

ASTM D4034 Seam Slippage: meets requirements

**LOW VOC** GREENGUARD Certified, GREENGUARD Gold Certified

**CONSTRUCTION WASTE MANAGEMENT** May be recyclable through reclamation

**ADDITIONAL PRODUCT ATTRIBUTES** Manufacturing materials recovery and reuse program

**CUSTOM CAPABILITIES** Custom backing is available

**MANUFACTURING** ISO 9001

**WARRANTY** Product is certified to be free of manufacturing defects for a period of two years from date of purchase when installed according to manufacturer's installation instructions

