

**WIDTH** 54" (137 cm)

**CONTENTS** 70% wood pulp, 30% polyester

**CERTIFIED WOOD** FSC certified (wood pulp)

**FINISH** Stain repellent

**PATTERN MATCH** Non-reverse hang unless otherwise noted on the roll, random match

**FIRE TEST** ASTM E84 Tunnel Test: Class A, flame spread 25, smoke developed 15 (test procedure is comparable to UL 723)

European Standard EN 13501 Fire Test: reaction to fire classification B-s2, d0

LIGHTFASTNESS ISO 105-B02, Heraeus original Hanau Xenotest 150S, minimum 6 on the standard blue scale

BS 8493 Light Reflectance Value: test on file

**PERMEABILITY** ASTM E96 Water Vapor Transmission Rate: test on file

LOW VOC ASTM D5197/D6196: test on file

**SPECIAL NOTE** Irregularities in texture and color are a feature of natural fibers used in the creation of this product. There can be a variation between the sample material and delivered product.

Please note that this material is not returnable.

ADDITIONAL PRODUCT ATTRIBUTES All dyeing, printing, laminating, embossing, finishing, etc., is water based

**WARRANTY** Manufacturer warrants that for a period of five years from the delivery of its wallcovering, products shall not separate from their backings when properly installed on a sound interior wall, adequately maintained and used under normal conditions

**SPECIAL INSTALLATION INSTRUCTION** Light-colored wallcoverings will require the underlying wall surface to be of a uniform color





