

silence

ACOUSTIC
WALLCOVERING

WEIGHT 30 oz/ly (930 g/lm)

WIDTH 54" (137 cm)

ROLL LENGTH 24 linear yards (21.5 meters)

FIBER 50% polyester, 50% polypropylene

RECYCLED CONTENT 43.3% recycled content by weight (polyester)

BACKING Latex

THICKNESS 0.375" (0.95 cm)

ABRASION RESISTANCE ASTM D3884: meets requirements

FIRE TEST ASTM E-84 Tunnel Test: Class A, flame spread 20, smoke developed 180 (test procedure is comparable to NFPA 255 and UL 723)

NFPA 265 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

COLORFASTNESS AATCC-165 Colorfastness to Wet & Dry Crocking: Class 5

TEAR STRENGTH ASTM D2261: meets requirements

TENSILE STRENGTH ASTM D5034: meets requirements

SOUND ABSORPTION ASTM C423 Reverberation Room Method: noise reduction coefficient (NRC) 0.20, sound absorption average (SAA) 0.22

ELECTROSTATIC AATCC Test Method 134, under 0.3 kV at 20% RH, 70°F: suitable for commercial use

CONSTRUCTION WASTE MANAGEMENT Recyclable through reclamation

ADDITIONAL PRODUCT ATTRIBUTES

Covers concrete block with proper preparations
Holes disappear once tacks are removed
Manufacturing materials recovery and reuse program
Minimal static-generating propensity
Reduces noise
Velcro compatibility, exhibits slight pilling

WARRANTY Product is certified to be free of manufacturing defects for a period of one year from date of purchase when installed according to manufacturer's installation instructions

