## synthesis fusion EUROPEAN PRINTS AND LASER-CUT DESIGNS

wIDTH 54" (137 cm)

CONTENTS 70% wood pulp, 30% polyester

**CERTIFIED WOOD** FSC certified (wood pulp)

FINISH Stain repellent

PATTERN MATCH Non-reverse hang unless otherwise noted on the roll, 10 1/8" (25.5 cm) vertical repeat, straight across match

FIRE TEST ASTM E84 Tunnel Test: Class A, flame spread 20, smoke developed 35 (test procedure is comparable to UL 723)

European Standard EN 13501 Fire Test: reaction to fire classification B-s1, d0

LIGHTFASTNESS ISO 105-B02, Heraeus original Hanau Xenotest 150S, minimum 6 on the standard blue scale

BS 8493 Light Reflectance Value: test on file

**PERMEABILITY** ASTM E96 Water Vapor Transmission Rate: test on file

LOW VOC ASTM D5197/D6196: test on file

SPECIAL NOTE Irregularities in texture and color are a feature of natural fibers used in the creation of this product. There can be a variation between the sample material and delivered product.

Please note that this material is not returnable.

ADDITIONAL PRODUCT ATTRIBUTES All dyeing, printing, laminating, embossing, finishing, etc., is water based

WARRANTY Manufacturer warrants that for a period of five years from the delivery of its wallcovering, products shall not separate from their backings when properly installed on a sound interior wall, adequately maintained and used under normal conditions

SPECIAL INSTALLATION INSTRUCTION Light-colored wallcoverings will require the underlying wall surface to be of a uniform color. Use a rubber roller instead of a spatula.

**COORDINATE** Visit Synthesis for solid coordinate options







Eykon tri kes 800 200 8120

800 433 0790