



## Tailored Silk

---

**Description:** Type II, W-101 (Fed. Spec. CCC-W-408A/D)

---

**Weight:** 20 oz.

---

**Width:** 52/54"

---

**Content:** 90% vinyl, 10% post industrial recycled vinyl

---

**Backing:** Osnaburg

---

**Installation:** Non-reverse hang, random match

---

**Repeat:** -

---

**Flame Resistance:** ASTM E84 Class A, CAN/ULC S102

---

**Permeability:** Specify microventing as an added feature for breathability

---

**Maintenance:** Warm water, mild soap

---

**Bleach Cleanable:** 10:1 water to bleach solution

---

©2024

---

Visit [momentumtextilesandwalls.com](https://momentumtextilesandwalls.com) to view full pattern repeat and complete specs

---

**PRODUCT USE ADVISORY** This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

### REDUCED ENVIRONMENTAL IMPACT:

- Phthalate free
- Prop 65
- GREENGUARD certified  
Low-VOC CA Section 01350
- EPD/HPD
- Recycled content

Pattern Detail

