

# bay ridge

TYPE II  
WALLCOVERING

**TYPE II** High durability, CCC-W-408A and W-101

**WEIGHT** 21 oz/ly (651 g/lm)

**WIDTH** 54" (137 cm)

**ROLL LENGTH** 30 linear yards (27.4 meters) sold in 15 yard (13.7 meter) increments only

**CONTENTS** 100% vinyl

**BACKING** Osnaburg

**PATTERN MATCH** Reverse hang, random match

**FIRE TEST** ASTM E84 Tunnel Test: Class A, flame spread 25, smoke developed 45 (test procedure is comparable to UL 723)

CAN/ULC S102 Tunnel Test: flame spread 0, smoke developed 20

NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

European Standard EN 13501 Fire Test: reaction to fire classification B-s2, d0

IMO (International Maritime Organization) Fire Test: United States Coast Guard Approved

**LOW VOC** California Section 01350

**CONSTRUCTION WASTE MANAGEMENT** May be recyclable through reclamation

**MICROVENTING AVAILABLE** This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

#### ADDITIONAL PRODUCT ATTRIBUTES

Antimicrobial additives  
Cadmium and mercury free  
Contains no heavy metals  
Does not contain DEHP plasticizers  
Free of PBDE's (Brominated Flame Retardants)  
Manufacturing materials recovery and reuse program  
Water-based inks

**CUSTOM CAPABILITIES** Custom colors and weights are available

**WARRANTY** Manufacturer warrants to the customer that the product will be free from defects in material and workmanship for a period of three years from the date of sale

**PRODUCT USE ADVISORY** This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

