

exclusive

prosper

TYPE II
WALLCOVERING

TYPE II High durability, CCC-W-408D and W-101

WEIGHT 20 oz/ly (620 g/lm)

WIDTH 54" (137 cm)

CONTENTS 100% vinyl

BACKING Osnaburg

PATTERN MATCH Non-reverse hang, 18" (45.5 cm) vertical repeat, straight across match

FIRE TEST ASTM E84 Tunnel Test: Class A, flame spread 20, smoke developed 95 (test procedure is comparable to NFPA 255, UBC 8-1 and UL 723)

CAN/ULC S102 Tunnel Test: flame spread 0, smoke developed 30

NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

European Standard EN 13501 Fire Test: reaction to fire classification B-s2, d0

ENVIRONMENTAL STANDARDS

Environmental Product Declaration (EPD)

HEALTH STANDARDS

Health Product Declaration (HPD)
Low VOC California Section 01350

CONSTRUCTION WASTE MANAGEMENT May be recyclable through reclamation

MICROVENTING AVAILABLE This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

ADDITIONAL PRODUCT ATTRIBUTES

Cadmium and mercury free
Contains no heavy metals
Does not contain DEHP plasticizers
Free of PBDE's (Brominated Flame Retardants)
Phthalate free
Water-based inks

CUSTOM CAPABILITIES Custom colors and weights are available

WARRANTY Manufacturer warrants that for a period of five years from the sale of its wallcovering products that the products shall be free of manufacturing defects, and that products shall not separate from their backings, and/or exhibit stains caused by bleeding of impurities

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

