

# conquer



**HIGH DURABILITY** Scrubbability, washability, tear and tensile strength meets or exceeds W-101 Type II

**WIDTH** 39 3/8" (100 cm)

**ROLL LENGTH** 11 linear yards (10 meters) sold in full rolls only

**CONTENTS** 100% coated glass fiber

**PATTERN MATCH** Reverse hang, random match

**FIRE TEST** ASTM E84 Tunnel Test: Class A, flame spread 20, smoke developed 5 (test procedure is comparable to UL 723)

CAN/ULC S102 Tunnel Test: flame spread 10, smoke developed 15

European Standard EN 13501 Fire Test: reaction to fire classification B-s1, d0

**IMO** Meets IMO (International Maritime Organization) requirements

**PERMEABILITY** ASTM E96 Water Vapor Transmission

**SUSTAINABILITY** OEKO-TEX® Standard 100, Novelio® CleanAir

**LOW VOC** California Section 01350, French VOC Regulation: meets requirements A+

**MANUFACTURING** ISO 9001, ISO 14001

**WARRANTY** Product is guaranteed to be free of defects in workmanship and material for five years


**SPECIAL INSTALLATION INSTRUCTION** For best results, the drywall surface should be finished to a level 4 prior to installation



## CleanAir technology removes formaldehyde from the air

How does it work?

1. FORMALDEHYDE ABSORPTION
2. PERMANENTLY CAPTURED
3. NEVER RELEASED



## Low VOC

## Breathable without perforation

- Woven glass fiber with natural breathability

## Natural durability of decorated glass fiber

- Made with non-toxic chemicals certified by OEKO-TEX® Standard 100
- Lightweight for lower transport costs but as strong as a Type III vinyl wallcovering
- Perfectly colorfast
- Scrubbable and does not absorb water
- Impact resistant