

exclusive

gradient/grade

TYPE II
WALLCOVERING

TYPE II High durability, CCC-W-408D and W-101

WEIGHT 20 oz/ly (620 g/lm)

WIDTH 54" (137 cm)

CONTENTS 100% vinyl: Colors 02-05, 07-10; Vinyl, polyester/metal: Colors 01, 06

RECYCLED CONTENT 7% post-consumer recycled content by weight (non-woven backing only)

BACKING Osnaburg: Colors 02-05, 07-10; Non-woven: Colors 01, 06

PATTERN MATCH Installation of Gradient and/or Grade is based on pattern layout provided by specifier using our interactive layout builder online at gradient.dlcouch.com

Gradient: Specify reverse hang, non-reverse hang or railroaded, 52" (132 cm) horizontal repeat, random match

Grade: Reverse hang, random match

FIRE TEST 100% vinyl: ASTM E84 Tunnel Test: Class A, flame spread 15, smoke developed 10 (test procedure is comparable to UL 723); CAN/ULC S102 Tunnel Test: flame spread 15, smoke developed 75; NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

Vinyl, polyester/metal: ASTM E84 Tunnel Test: Class A, flame spread 25, smoke developed 55 (test procedure is comparable to UL 723)

LOW VOC California Section 01350, SCS Indoor Advantage™ Gold

CONSTRUCTION WASTE MANAGEMENT 100% vinyl may be recyclable through reclamation

MICROVENTING AVAILABLE This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

SPECIAL NOTE Colors 01 and 06 may interfere with broadcast signals, such as Wi-Fi and radio reception. While interference is possible because of the polyester/metal layer in this specific construction, tests have shown a 5% or less impact on signals when the receptor is totally encased in wallcovering.

ADDITIONAL PRODUCT ATTRIBUTES Antimicrobial additives, Cadmium and mercury free, Contains no heavy metals, Does not contain DEHP plasticizers, Free of PBDE's (Brominated Flame Retardants), Manufacturing materials recovery and reuse program, Water-based inks

CUSTOM CAPABILITIES Custom colors, weights and widths are available

WARRANTY Manufacturer warrants that for a period of five years from the installation of its commercial wallcovering there shall not be separation from their backings, exhibit stains caused by bleeding of impurities or support the growth of mildew when wallcoverings are installed properly on a sound wall, adequately maintained and used under normal conditions

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

SPECIAL INSTALLATION INSTRUCTION Colors 01 and 06 contain metallic particles and will conduct electricity. To avoid possible fire hazards or electric shock, wallcovering should not come in contact with or extend into electrical-outlet boxes or light-switch boxes. Turn off all electricity to the room prior to starting installation.