

# polaris

RECYCLED  
WALLCOVERING

**WIDTH** 54" (137 cm) plus selvage

**CONTENTS** 65% polyester, 35% olefin

**RECYCLED CONTENT** 29% pre-consumer recycled content by weight (olefin)

**BACKING** Acrylic/latex

**FINISH** Stain repellent

**PATTERN MATCH** Non-reverse hang, random match

**FIRE TEST** ASTM E84 Tunnel Test: Class A, flame spread 20, smoke developed 50 (test procedure is comparable to ANSI/UL 723, NFPA 255 and UBC 8-1)

CAN/ULC S102 Tunnel Test: flame spread 5, smoke developed 20

UBC 8-2 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

**COLORFASTNESS**

AATCC-16 Colorfastness to Light: Class 4.0, 40 hours

AATCC-8 Colorfastness to Wet & Dry Crocking: meets requirements

**PERMEABILITY** ASTM E96 Water Vapor Transmission Rate: test on file

**TEAR STRENGTH** ASTM D2261: test on file

**TENSILE STRENGTH** ASTM D5034: test on file

**ACOUSTICAL VALUE** Acoustically transparent; ASTM C423 Reverberation Room Method: noise reduction coefficient (NRC) 0.55 with tested acoustical backer board

**ADDITIONAL TESTS**

ASTM D434 Seam Slippage: test on file

**CONSTRUCTION WASTE MANAGEMENT** May be recyclable through reclamation

**ADDITIONAL PRODUCT ATTRIBUTES** Manufacturing materials recovery and reuse program

**CUSTOM CAPABILITIES** Custom backing, colors, and widths are available

**WARRANTY** Product is certified to be free of manufacturing defects for a period of five years from date of purchase when installed according to manufacturer's installation instructions

