

mayfair

ACOUSTIC
WALLCOVERING

WEIGHT 24 oz/ly (744 g/lm)

WIDTH 52" (132 cm) plus selvage

ROLL LENGTH 33 linear yards (30.2 meters)

FIBER 100% recycled polyester

RECYCLED CONTENT 95% minimum post-consumer recycled content by weight (Eco-fi® polyester), remaining fiber is pre-consumer (polyester)

BACKING Fused polyester

THICKNESS 1/8" (0.5 cm)

PATTERN MATCH Non-reverse hang, 1/2" (1.5 cm) horizontal repeat, 1/8" (0.5 cm) vertical repeat, straight across match

FIRE TEST ASTM E84 Tunnel Test: Class A, flame spread 10, smoke developed 95 (test procedure is comparable to ANSI/UL 723, NFPA 255 and UBC 8-1)

NFPA 265 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

COLORFASTNESS

AATCC-16 Colorfastness to Light: Class 4, 40 hours

AATCC-8 Colorfastness to Wet & Dry Crocking: test on file

MOISTURE REGAIN ASTM D2654: test on file

PERMEABILITY ASTM E96 Water Vapor Transmission Rate: test on file

SOUND ABSORPTION ASTM C423 Reverberation Room Method: noise reduction coefficient (NRC) 0.25, sound absorption average (SAA) 0.25

LOW VOC California Section 01350

CONSTRUCTION WASTE MANAGEMENT May be recyclable through reclamation

ADDITIONAL PRODUCT ATTRIBUTES

Antimicrobial additives
Covers concrete block with proper preparations
Holes disappear once tacks are removed
Manufacturing materials recovery and reuse program
Minimal static-generating propensity
Reduces noise

CUSTOM CAPABILITIES Custom colors are available

MANUFACTURING ISO 9001

WARRANTY Manufacturer warranties wallcovering to be free from manufacturing defects for a period of five years from date of purchase

