

exclusive

# heirloom

TYPE II  
WALLCOVERING

**TYPE II** High durability, CCC-W-408D and W-101

**WEIGHT** 20 oz/ly (620 g/lm)

**WIDTH** 50" (127 cm)

**CONTENTS** 100% vinyl

**BACKING** Osnaburg

**PATTERN MATCH** Non-reverse hang, 33 1/2" (85 cm) vertical repeat, straight across match

**FIRE TEST** ASTM E84 Tunnel Test: Class A, flame spread 20, smoke developed 235 (test procedure is comparable to ANSI 2.5, NFPA 255, UBC 42-1 and UL 723)

CAN/ULC S102 Tunnel Test: flame spread 5, smoke developed 40

NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

European Standard EN 13501 Fire Test: reaction to fire classification B-s2, d0

**ENVIRONMENTAL STANDARDS**  
Environmental Product Declaration (EPD)

**HEALTH STANDARDS**  
Health Product Declaration (HPD)  
Low VOC California Section 01350

**CONSTRUCTION WASTE MANAGEMENT** May be recyclable through reclamation

**MICROVENTING AVAILABLE** This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

**MINIMUM** Material is made to order (not stocked). Order by the yard after 10 yard (9.1 meter) minimum is met. Please allow 3-4 weeks for delivery.

**SPECIAL NOTE** Since each order is made to order, NO RETURNS WILL BE ACCEPTED

**ADDITIONAL PRODUCT ATTRIBUTES**  
Cadmium and mercury free  
Contains no heavy metals  
Does not contain DEHP plasticizers  
Free of PBDE's (Brominated Flame Retardants)  
Phthalate free  
Solvent-based inks

**CUSTOM CAPABILITIES** Custom colors are available

**WARRANTY** Manufacturer warrants that for a period of five years from the sale of its wallcovering products that the products shall be free of manufacturing defects, and that products shall not separate from their backings, and/or exhibit stains caused by bleeding of impurities

**PRODUCT USE ADVISORY** This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

