

PATTERN INFORMATION

Type:	Type II
Width:	52/54 in (132.08/137.16 cm)
Weight:	25.0 oz per lineal yard
Backing:	Cotton Scrim
Installation:	Reversible with a random match
Vertical Repeat:	Not applicable
Horizontal Repeat:	Not applicable
Custom Colors/Weights Available*:	Type II: 500 yard min.
Minimum Custom Weight/Backing*:	Type II: 25.0 oz cotton scrim
Custom Microventing (Perforation) available*:	Contact distributor for minimums

*Subject to Custom Production Coverage %

PATTERN SPECIFICATIONS

	U.S.	Metric
Finished Total Weight:		
*19.5 oz per lineal yard	25.0 oz/ly	775 g/lm
*13.0 oz per square yard	17.3 oz/sq yd	587 g/sq m
Vinyl Weight:		
*7.0 oz per square yard	21.33 oz/ly	660 g/lm
Backing Fabric Weight:	3.0 oz/ly	93 g/lm
Tensile Breaking Strength:	Exceeds min. Type II Specifications	
*50 x 55 lbs – 222 x 245 N		
Tear Strength:	Exceeds min. Type II Specifications	
*25 x 25 Scale Reading		
Average Adhesion Vinyl to Fabric:	Exceeds min. Type II Specifications	
*3 lb/in – 13.4 N/25mm		

*Minimum specification requirement

FIRE CLASSIFICATION

Flame	5
Smoke	40
Passes ASTM E84 (GRC) & NFPA 286	

ENVIRONMENTAL

Low VOC. Meets California Section 01350 Indoor Air Quality Standard.
 Can contribute to LEED® EQ 4.1 point for low-emitting materials, adhesives, and sealants if used with low VOC adhesives.
 Can Contribute to LEED® MR 5.1 point for regional materials.
 Manufactured using comprehensive raw material recycling.
 Made with highly cleanable water-based inks.
 Contains no cadmium or mercury-based pigments. Pigments are fade and alkali-resistant.

OTHER FEATURES

Made in the USA
 Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM-G21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. Perforation is available for enhanced permeability.

PRODUCT USE ADVISORY

This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it very low in permeability. Vinyl wallcovering products should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

