

PATTERN INFORMATION

Type:	Type II
Width:	52/54 in (132.08/137.16 cm)
Weight:	20.0 oz per lineal yard
Backing:	Osnaburg
Installation:	Reversible with a random match
Vertical Repeat:	Not applicable
Horizontal Repeat:	Not applicable
Custom Colors/Weights Available*:	Type I: 1000 yard min. Type II: 400 yard min.
Minimum Custom Weight/Backing*:	Type I: 15.0 oz Type II: 20.0 oz
Custom Microventing (Perforation) available*:	Contact distributor for minimums

*Subject to Custom Production Coverage %

PATTERN SPECIFICATIONS

	U.S.	Metric
Finished Total Weight:		
*19.5 oz per lineal yard	20.0 oz/ly	620 g/lm
*13.0 oz per square yard	13.3 oz/sq yd	452 g/sq m
Vinyl Weight:		
*7.0 oz per square yard	17.0 oz/ly	526 g/lm
Backing Fabric Weight:	3.0 oz/ly	93 g/lm
Tensile Breaking Strength:	Exceeds min. Type II Specifications	
*50 x 55 lbs - 222 x 245 N		
Tear Strength:	Exceeds min. Type II Specifications	
*25 x 25 Scale Reading		
Average Adhesion Vinyl to Fabric:	Exceeds min. Type II Specifications	
*3 lb/in - 13.4 N/25mm		

*Minimum specification requirement

FIRE CLASSIFICATION

Flame	20
Smoke	45

Passes ASTM E84 (GRC), NFPA 286 Corner Burn & CAN/ULC S102.2

ENVIRONMENTAL

Low VOC. Meets California Section 01350 Indoor Air Quality Standard.
Can contribute to LEED® EQ 4.1 point for low-emitting materials, adhesives, and sealants if used with low VOC adhesives.
Can Contribute to LEED® MR 5.1 point for regional materials.
Manufactured using comprehensive raw material recycling.
Made with highly cleanable HAPs Free solvent-based inks.
Contains no cadmium or mercury-based pigments. Pigments are fade and alkali-resistant.

OTHER FEATURES

Made in the USA
GSA Fed. Spec. CCC-W-408D & W-101
Contains anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM-G21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. Perforation is available for enhanced permeability.

PRODUCT USE ADVISORY

This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it very low in permeability. Vinyl wallcovering products should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

