



● aluminio

specialty wallcovering

UNIQUE WALLCOVERING	
Width 36" untrimmed	Backing Paper
Roll Length 8 linear yards sold in full rolls only	Facing Metal
Fire classification ASTM E-84 Class A	Special Notes As with all natural, hand-made wallcovering, color variation is normal. Avoid direct or brightly reflected sunlight. Not guaranteed against fading or color change.
Special Installation Instructions: This wallcovering contains metallic particles and will conduct electricity. To avoid possible fire hazards or electric shock, wallcovering should not come in contact with or extend into electrical outlet boxes or light switch boxes. Turn off all electricity to the room prior to starting installation. For best results, the drywall surface should be finished to a level 4 prior to installation and the material should be hung using heavy-duty clear adhesive. Never use a seam roller directly on the surface of the wallcovering.	


Product Use Advisory

This wallcovering contains metallic particles and will conduct electricity. To avoid possible fire hazards or electric shock, wallcovering should not come in contact with or extend into electrical outlet boxes or light switch boxes.

This product is intended for use in buildings designed and maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates.

The construction that makes Aluminio wallcovering a beautiful metal surface also renders it very low in permeability. Aluminio wallcovering products should not be installed on walls that contain excessive moisture or are subject to moisture infiltration. If mold or mildew is present, or if the walls show moisture damage or have excess moisture content, do not proceed with installation. Moisture infiltration and water vapor in and behind the wall must be eliminated for proper performance. In addition, the use of a mildew inhibitor in the primer is highly recommended.

After installation, the walls and wallcovering should be monitored for potential moisture or water vapor infiltration and accumulation. Any such infiltration or accumulation after installation must be promptly eliminated.



Aluminio wallcovering, by nature, is impermeable

D.L.Couch

800 433 0790

Eykon

800 222 7866

trikes

800 200 8120

please call for larger samples



trikes

800 200 8120 tel
800 430 8120 fax
trikes.com

● aluminio installation

specialty wallcovering

Inspect goods carefully. Additional rolls from this dye-lot may not be available. No returns on cut goods.

Confirm that you have the correct color and wallcovering before installing.

No claims allowed for labor charges or consequential damages under any condition.

Wallcovering can display certain irregularities which are inherent to the manufacturing process.

Preparation

This is a natural product. Color variation is normal. Please carefully grade for color flow before installing.

Prepare wall with oil-based flat primer to mirror smoothness. Primer may be color blended to match wallcovering. DO NOT paint primer too thick, so moisture from paste can evaporate. Walls must be completely dry before hanging.

Adhesive

Use pre-mixed, heavy-duty, clear vinyl paste, e.g. Shur-stik 780. It will take time, up to one week, for adhesive to completely dry out.

Installation

Trim with a very sharp razor blade.

Make sure paste is spread evenly and adequately over entire back of wallcovering.

Apply paste thicker to edges to avoid seams opening.

DO NOT fold after pasting, as the creases may be difficult to smooth out.

Smooth with a soft brush. DO NOT rub face of paper with a stiff brush.

Immediately wipe off excess paste with a soft, damp cloth and then with a dry cloth.

Never use a roller directly on the surface of the wallcovering.

Booking Time

It is essential to allow wallcovering sufficient relaxing time to avoid bubbling, shrinking and seam opening. Allow the paste enough time to soak (relax) into a sheet before hanging. Usual relaxing time is 5-10 minutes. Do a small test strip to determine the proper relaxing time.

Note

Avoid excessively soaking paper. Do not pull panels once they have been placed on the wall. Either of these may cause seams to open during drying.

Avoid direct or brightly reflected sunlight. Not guaranteed against fading or color change.

Cleaning

Materials can be cleaned with a soft, moist cloth. Do not scrub, use any chemicals or any abrasive cleaning agents on these natural materials.