

Akasha

VERSA
WALLCOVERING

Application: Wallcovering

Description: Type II, W-101 (Fed. Spec. CCC-W-408A/D)

Weight: 20 oz.

Width: 52/54"

Content: 98% vinyl, 2% metallized polyester; *100% vinyl

Backing: Non-woven; *Osnaburg

Installation: Non-reverse hang, random match

Flame Resistance: ASTM E84 Class A;
*ASTM E84 Class A, CAN/ULC S102

Permeability: *Specify microventing as an added feature for breathability

Maintenance: Warm water, mild soap

©2020

Visit memosamples.com to view full pattern repeat and complete specs

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

Akasha's color palette is designed with two techniques creating unique specifications.

*Denotes the specifications for SKU A201-014

REDUCED ENVIRONMENTAL IMPACT:

- Phthalate free
- Prop 65
- GREENGUARD certified
Low-VOC CA Section 01350
- HPD; *EPD/HPD
- NSF/ANSI 342 certified
- Water-based inks



A201-548 Hyperion