



Application: Wallcovering

Description: Type II, W-101 (Fed. Spec. CCC-W-408A/D)

Weight: 20 oz.

Width: 52/54"

Content: 100% vinyl; *98% vinyl, 2% metallized polyester

Backing: Osnaburg; *Non-woven

Installation: Reverse hang, pattern alignment; refer to installation instructions

Repeat: -

Flame Resistance: ASTM E84 Class A, CAN/ULC S102;
*ASTM E84 Class A

Permeability: Specify microventing as an added feature for breathability to 100% vinyl SKUs

Maintenance: Warm water, mild soap

Bleach Cleanable: 10:1 solution

©2021

Visit memosamples.com to view full pattern repeat and complete specs

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

Avenir is designed with two techniques creating unique specifications.

*Denotes the specifications for SKUs A204-522, A204-775, A204-519, A204-581, and A204-323

REDUCED ENVIRONMENTAL IMPACT:

- Phthalate free
- Prop 65
- GREENGUARD certified
Low-VOC CA Section 01350
- EPD/HPD; *HPD
- NSF/ANSI 342 certified
- Water-based inks



A204-522 Twilight



memosamples.com | 800.366.6839

MOMENTUM
TEXTILES & WALLCOVERING