

VANTAGE III

Verdon

Description: Meets or exceeds all Type III requirements of CCC-W-408A/D and W-101

Weight: 33 oz.

Width: 52/54"

Thickness: .034"

Content: 70% olefin composite, 30% post-industrial recycled olefin composite

Backing: Drill

Finish: Assure Surface Protection

Installation: Reverse hang, random match

Repeat: -

Flame Resistance: ASTM E84 Class A

Hoffman Scratch Resistance: 2000 g

Abrasion Resistance: ASTM D4060: <.05% (weight loss)

Tear Resistance: ASTM D1922: >3200 g

Tensile Strength: ASTM D751 (modified method): 130/100 lbs

Stain Resistance: ASTM D1308: 10

Chemical Resistance: ASTM D543: 9

Maintenance: Request detailed instructions

Bleach Cleanable: 10:1 water to bleach solution

©2022 Versa Designed Surfaces

Visit memosamples.com to view full pattern repeat and complete specs

REDUCED ENVIRONMENTAL IMPACT:

- evo® PVC-free technology
- Phthalate free
- Prop 65
- GREENGUARD certified
Low-VOC CA Section 01350
- HPD
- Recycled content
- Water-based inks

VERSA
DESIGNED SURFACES



AFPO4-886 Smoke



memosamples.com | 800.366.6839

MOMENTUM
TEXTILES & WALLCOVERING