VERSA WALLCOVERING

## **Emerson** Texture

Description:	Type II, W-101 (Fed. Spec. CCC-W-408A/D)
Weight: 20 d	DZ.
Width: 52/5	4″
Content: 100	D% vinyl
Backing: Osr	naburg
Installation:	Reverse hang, random match
Repeat: -	
Flame Resista	ance: ASTM E84 Class A, CAN/ULC S102
Permeability: breathability	Specify microventing as an added feature for
Maintenance	: Warm water, mild soap
Bleach Clean	able: 10:1 water to bleach solution
©2022 Vers	a Designed Surfaces
Visit memosar complete spec	nples.com to view full pattern repeat and

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

## **REDUCED ENVIRONMENTAL IMPACT:**

- Phthalate free
- Prop 65
- GREENGUARD certified Low-VOC CA Section 01350
- EPD/HPD
- NSF/ANSI 342 certified
- Water-based inks



A205-038 Heather



MOMENTUM TEXTILES & WALLCOVERING