

Englewood

Description: Type II, W-101 (Fed. Spec. CCC-W-408A/D)

Weight: 20 oz.

Width: 52/54"

Content: 80% olefin composite, 20% post-industrial recycled olefin composite

Backing: Osnaburg

Installation: Non-reverse hang, random match

Repeat: -

Flame Resistance: ASTM E84 Class A, CAN/ULC S102

Permeability: Specify microventing as an added feature for breathability

Maintenance: Warm water, mild soap

Bleach Cleanable: 10:1 water to bleach solution

©2022 Versa Designed Surfaces

Visit [memosamples.com](https://www.memosamples.com) to view full pattern repeat and complete specs

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make wallcovering cleanable and durable also render it low in permeability. Wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

REDUCED ENVIRONMENTAL IMPACT:

- evo[®] PVC-free technology
- Phthalate free
- Prop 65
- GREENGUARD certified
Low-VOC CA Section 01350
- HPD
- Recycled content
- Water-based inks



AVF20-584 Thistle

