

TYPE II coordinate to **Exhale**

Item # FBV-20335 - FBV-20343 (6 colorways)

LOW VOC **RECYCLED CONTENT**

PHYSICAL PROPERTIES

Weight 20 oz. PLY/620 G/PLM
13.3 oz. PSY/451 G/PSM
Width 54"/137 cm
Backing Osnaburg
Match Straight Random
Repeat N/A
Custom colors and micro venting available
Meets or exceeds Federal Specification CCC-W-408D

FIRE SAFETY

- Class "A" Fire rated – Tested in accordance with ASTM E-84 Tunnel Test
- Passes Class "A" NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test

See website or contact us for additional results

ENVIRONMENT & HEALTH

- 10% recycled content (varied blend of pre-consumer and remanufactured material)
- Meets California Section 01350 IAQ test requirements for wallcovering
- Complies with USGBC LEED v4 Criteria, under Indoor Environmental Quality (CDPH/EHLB/Standard Method Version 1.1, 2010)Warranty

ANTIMICROBIAL FEATURES

Wallcovering contains antimicrobial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. All wallcoverings can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

WARRANTY

5 year warranty against manufacturing defects.



MOMENTUM
TEXTILES & WALLCOVERING

memosamples.com | 800.366.6839