

## VANTAGE III

### Lima

**Description:** Meets or exceeds all Type III requirements of CCC-W-408A/D and W-101

**Weight:** 33 oz.

**Width:** 52/54"

**Thickness:** .034"

**Content:** 70% olefin composite, 30% post-industrial recycled olefin composite

**Backing:** Drill

**Finish:** Assure Surface Protection

**Installation:** Reverse hang, random match

**Repeat:** -

**Flame Resistance:** ASTM E84 Class A

**Hoffman Scratch Resistance:** 2000 g

**Abrasion Resistance:** ASTM D4060: <.05% (weight loss)

**Tear Resistance:** ASTM D1922: >3200 g

**Tensile Strength:** ASTM D751 (modified method): 130/100 lbs

**Stain Resistance:** ASTM D1308: 10

**Chemical Resistance:** ASTM D543: 9

**Maintenance:** Request detailed instructions

**Bleach Cleanable:** 10:1 water to bleach solution

©2022 Versa Designed Surfaces

Visit [memosamples.com](https://memosamples.com) to view full pattern repeat and complete specs

#### REDUCED ENVIRONMENTAL IMPACT:

- evo® PVC-free technology
- Phthalate free
- Prop 65
- GREENGUARD certified  
Low-VOC CA Section 01350
- HPD
- Recycled content
- Water-based inks

**VERSA**  
DESIGNED SURFACES



AFPO5-368 Pacific

