

VANTAGE II

Elodie

Description: Exceeds Type II requirements of CCC-W-408A/D and W-101

Weight: 20 oz.

Width: 52/54"

Thickness: .021"

Content: 80% olefin composite , 20% post-industrial recycled olefin composite

Backing: Osnaburg

Finish: Assure Surface Protection

Installation: Reverse hang, random match

Repeat: -

Flame Resistance: ASTM E84 Class A

Hoffman Scratch Resistance: 2000 g

Abrasion Resistance: ASTM D4060: <.05% (weight loss)

Tear Resistance: ASTM D1922: >1050 g

Tensile Strength: ASTM D751 (modified method): 90/80 lbs

Stain Resistance: ASTM D1308: 10

Chemical Resistance: ASTM D543: 9

Maintenance: Request detailed instructions

Bleach Cleanable: 10:1 water to bleach solution

©2023 Versa Designed Surfaces

Visit momentumtextilesandwalls.com to view full pattern repeat and complete specs

REDUCED ENVIRONMENTAL IMPACT:

- evo® PVC-free technology
- Phthalate free
- Prop 65
- GREENGUARD certified
Low-VOC CA Section 01350
- HPD
- Recycled content
- Water-based inks



AVF22-259-ASP Reverie

VERSA
DESIGNED SURFACES