Type II Clean Vinyl Wallcovering



On Track

Description: Type II, W-101 (Fed. Spec. CCC-W-408A/D)

Weight: 20 oz.

Width: 52/54"

Content: 100% vinyl

Backing: Non-woven, 50% post-consumer recycled content

Finish: York Defender® Premier Antimicrobial Protection

Installation: Non-reverse hang, straight-across match

Repeat: 251/4" V x 27" H

Flame Resistance: ASTM E84 Class A, CAN/ULC S102

Permeability: Specify microventing as an added feature for

breathability

Surface Finish: For best results, the drywall should be

finished to a level 5 prior to installation

Maintenance: Warm water, mild soap

Bleach Cleanable: 10:1 water to bleach solution

©2023

Visit momentumtextilesandwalls.com to view full pattern repeat and complete specs

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

REDUCED ENVIRONMENTAL IMPACT:

- Phthalate free
- Prop 65
- GREENGUARD certified Low-VOC CA Section 01350
- EPD
- NSF/ANSI 342 certified
- Recycled content
- Water-based inks





SG3090 Adventure

