Class "A" Fire rated - Tested in accordance with ASTM E-84 Tunnel Test

TYPE II coordinate to Madagascan Straw

Item # FBV-20365 - FBV-20380 (16 colorways)

LOW VOC RECYCLED CONTENT

Passes Class "A" NFPA 101 Life Safety Code

Passes NFPA 286 Corner Burn Test

See website or contact us for additional results

ANTIMICROBIAL FEATURES

PHYSICAL PROPERTIES

Weight 20 oz. PLY/620 G/PLM

13.3 oz. PSY/451 G/PSM

Width 54"

Backing Osnaburg

Match Reverse Random

Repeat N/A

Custom colors and micro venting available

Meets or exceeds Federal Specification CCC-W-408D

FIRE SAFFTY

Wallcovering contains antimicrobial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. All wallcoverings can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

ENVIRONMENT & HEALTH

- 10% recycled content (varied blend of pre-consumer and remanufactured material)
- Meets California Section 01350 IAQ test requirements for wallcovering
- Complies with USGBC LEED v4 Criteria, under Indoor Environmental Quality (CDPH/EHLB/Standard Method Version 1.1, 2010) Warranty

WARRANTY

5 year warranty against manufacturing defects.



memosamples.com | 800.366.6839