

## South Beach Silk

Item # P3T-60425 - P3T-60439 (15 colorways)



Impact



Chemical



Abrasion

### PHYSICAL PROPERTIES


Width	Trim to 48"
Packaging	15-yd rolls
Thickness	0.032
Backing	Heavy Polyester/ Cotton knit
Repeat	N/A
Installation	Reverse Random
Fire Safety	Class "A" rated ASTM E-84; NFPA 286



Impact

Impact Resistance  
ASTM D- 5420-10  
Gardner Method

Pattern In-Lbs  
**South Beach Silk** +100



Chemical

Chemical Resistance  
ASTM D-1308  
Spot test covered 3.1.1

Cleaning Agents

Tide w/H2O

Virex

Ammonia

Isopropyl Alcohol

Goof Off

Fantastik

Lysol

Hydrogen Peroxide

Bleach

Methyl Ethyl Ketone

Results: No change in P3TEC surface from exposure to these agents.

Cleaning

ASTM F-793

SECTION 7.5

Staining Agents

Grape Juice

Mustard

Black Sharpie

Ink Pen

Betadine

Shoe Polish

Lipstick

Black Rubber

Brake Fluid

Spray Paint

Results: Each staining agent above was wiped clean with at least one listed cleaning agent.



Abrasion

Abrasion Resistance

ASTM D- 4060-14

Taber Method

Test Spec

CS-10F wheel

500 gram load @200 cycles

Weight loss: 0.02%

### ENVIRONMENTAL & HEALTH

Indoor Air	Meets California Section 01350
Fungal Resistant	ASTM G-21
Bacterial Resistant	ASTM G-22
HPD	third- party classified
EPD	third- party certified
Recycled content	
California Prop 65, no labeling required	
Non-phthalate	

Best stain removal results can be achieved by use of progressively strong, non-abrasive cleaners, and which can be supplemented by use of a soft bristle brush.

### OTHER

5 year warranty against manufacturing defects.

Accessories: Coordinating corner guards and Type II wallcovering (on selected colorways) available.

Installs with techniques similar to Type II vinyl wallcovering, including seaming with overlap and double-cut process.

See full Installation Instructions from distributor.

Sold in 15-yd coreless rolls, one per shipping box (approximately 42 lbs)



**MOMENTUM**  
TEXTILES & WALLCOVERING

memosamples.com | 800.366.6839